

SOAP - WSDL: <http://api.surveyanalytics.com/a/soap/v2?WSDL>

The following SOAP Method Calls are available: -

Enclosed are the Following Survey Analytics Calls:

- [GetSurveyNames](#)
- [GetRawData](#)
- [GetRawDataForAllSurveys](#)
- [GetSurveyResponseData](#)
- [SendSurveyToGroup](#)

surveyanalytics.GetSurveyNames		
Returns all the Active Surveys for the Account		
Parameters		
Name	Type	Description
username	String	The account username
password	String	The account password
Return		
Type	Description	
String[] (Array)	The Surveys for the account	

surveyanalytics.CreateEmailAddressGroup		
Creates a New Email Address Group. An Email Address Group is holder for storing email addresses. Use the groupCode for subsequent calls related to sending surveys etc.		
Parameters		
Name	Type	Description
username	String	The account username
password	String	The account password
groupName	String	The display name for the group
groupCode	String	The code for the group. Use this code for subsequent address-book related calls
Return		

Type	Description
Integer	0 - Successful 999 - Internal Server Error

surveyanalytics.GetSurveyTrackingURL

Returns the Unique URL to the Survey along with the necessary tracking information

Parameters

Name	Type	Description
username	String	The account username
password	String	The account password
surveyName	String	The survey name (See also surveyanalytics.GetSurveyNames)
groupCode	String	The code for the group. If a Group with this code already exists then the email address will be added to this group. If not, then a new group with this code will be created (See also surveyanalytics.CreateEmailAddressGroup)
emailAddress	String	The Email Address of the respondent

Return

Type	Description
String	The URL to send to the respondent

surveyanalytics.GetSurveyInHTML

Returns the HTML Code for the Survey

Parameters

Name	Type	Description
username	String	The account username
password	String	The account password
surveyName	String	The survey name (See also surveyanalytics.GetSurveyNames)

Return

Type	Description
String	The HTML Code for the survey

surveyanalytics.GetRawData

Returns the RAW (CSV) data for a timeperiod

Parameters

Name	Type	Description
username	String	The account username
password	String	The account password
surveyName	String	The survey name (See also surveyanalytics.GetSurveyNames)
startTime	dateTime.iso8601	Start Time
endTime	dateTime.iso8601	End Time

Return

Type	Description
String	The RAW data - Each response in a single line (Newline Delimiter)

surveyanalytics.GetRawDataForAllSurveys

Returns the RAW (CSV) data for a timeperiod for all the surveys in your account

Parameters

Name	Type	Description
username	String	The account username
password	String	The account password
startTime	dateTime.iso8601	Start Time
endTime	dateTime.iso8601	End Time

Return

Type	Description
String	The RAW data - Each response in a single line (Newline Delimiter)

surveyanalytics.GetSurveyResponseData

Returns the formatted HTML data for a contact (email address)

Parameters

Name	Type	Description
username	String	The account username
password	String	The account password
surveyName	String	The Name of the Survey

groupCode	String	The Name of the Email List
emailAddress	String	The Email Address to search for
Return		
Type	Description	
String	The HTML Formatted data for ALL RESPONSES linked to the email address	

surveyanalytics.SendSurveyToGroup		
Sends a survey invitation to a list of email addresses		
Parameters		
Name	Type	Description
username	String	The account username
password	String	The account password
surveyName	String	The Name of the Survey
groupCode	String	The Name of the Email List
emailAddress	String[]	The Email Addresses to send to
Return		
Type	Description	
Void		

www.surveyanalytics.com